

Multi Range,Multi Function Dual display Timer – 9D



SPECIFICATION :

Model	UT-9D
Over All Size	96*96*50 mm
Cut Out	92*92 mm
Mounting Type	Panel Mounting
I/P Supply	230VAC,+/-15%,50Hz.(Other Supply on Request)
Timing Range	999.9/99.99/9999 sec/Min/Hr (selectable)
Display Method	Upper = 4-Digit 0.56" RED or White 7-Segment LED display.for PV
	Lower= 4-Digit 0.39" GREEN 7-Segment LED LED display for SV.
Time Setting	Front Key Pad.
Operating Mode	On delay,Off delay,Forward,Reverse,Cyclic,(selectable)
Count Direction	UP or Down Selectable
Power Fail Memory	Yes/ NO Selectable
Start Logic	Power ON / Front Key/External Dry Contact/NPN-PNP Proximity S/W.
Reset	Front Key, Power interruption.or External start pulse.
Control O/P	1 C/O/ 2 C/O-Relay o/p (5A@230vac) or Isolated SSR o\p (+12vdc)
LED Indication	Relay status.
EMC Standard	EN50081-2 & EN 50082-2 Generic Stds for Industrial Environment
Safety Standards	Meets EN61010, Installation Catagory II

Multi Range, Multi Function Dual display Timer – 9D

Operating Ambient	0°C to 55°C
Storage Temperature	-10 to +70 °C
Operating Humidity	5~80%RH Non-condensing

Heatcon Automation