

Programmable 2-CH Bulk Milk Programmer



SPECIFICATION :

Model	BMC-74S
Over All Size	72*72*65 mm
Cut Out	68*68 mm
Mounting Type	Panel Mounting
Input Supply	230VAC, +/-15%,50Hz.(Other Supply On Request)
Display Method	4 Digit RED 7 Segment LED Display.
Temperature Sensor	RTD
Temperature Range	.-50°C to 50°C
Control Method	ON/OFF
Temperature Accuracy	0.25 % of FSR or 1°C Max, Software Calibrated Lineariser.
Display Resolution	0.1°C
Load Sensor	2-Nos High Accuracy Measuring CT
Display Resolution	0.1A
Load Indication Range	(a) Ageing Motor =9.9 A (b) Compressor =30A
Load Indication Accuracy	0.1 % of FSR .

Programmable 2-CH Bulk Milk Programmer

Setting Method	Front 3-Tact Switch Key
Function Keys	Front 2-Tact Switch Key
Control O/P	2-Nos-1 c/o Relay contact,3A@230VAC)
	(a) Agitator (b) Compressor
Digital I/P Signal	High-Pressure Trip
O/P Relay status	By front panel 4-LED indication.
Operating Ambient	0°C to 55°C
Storage Temperature	-10 to +70 °C
Operating Humidity	5~80%RH Non-condensing
EMC Standard	EN50081-2 & EN 50082-2 Generic Stds for Industrial Environment
Safety Standards	Meets EN61010, Installation Catagory II

Heatcon Automation