

# Programmable 2-CH-Time Constant based Filling Programmer



## SPECIFICATION :

<b>Model</b>	<b>SP-9LT</b>
<b>Over All Size</b>	96*96*50 mm
<b>Cut Out</b>	92*92 mm
<b>Mounting Type</b>	Panel Mounting
<b>I/P Supply</b>	230VAC, +/-15%, 50Hz. (Other Supply on Request)
<b>Range Selection</b>	00.000 / 000.00/0000.0/00000 Ltr/Min (Selectable)
<b>Calibration Method</b>	Digital calibration via a front keypad
<b>Display method</b>	Alphanumeric 16x2 Line Blue Backlit LCD (4.5mm character height).
<b>Status LED's</b>	5-Red LEDs.
<b>Key Operation</b>	14-Function Keys. (tactile feedback)
<b>Flow Measurement</b>	Time Constant base
<b>Digital Logic I/Ps.</b>	2-Nos Opto Isolated Logic I/P for start with +12VDC Ext.voltage for sensor..
<b>Control Relay O/Ps</b>	2-Nos of 1c/o Relay O/P (3A@230VAC)
<b>EMC Standard</b>	EN50081-2 & EN 50082-2 Generic Stds for Industrial Environment
<b>Safety Standards</b>	Meets EN61010, Installation Catagory II
<b>Operating Ambient</b>	0°C to 55°C

# Programmable 2-CH-Time Constant based Filling Programmer

<b>Storage Temperature</b>	-10 to +70 °C
<b>Operating Humidity</b>	5~80%RH Non-condensing

Heatcon Automation