

Programmable 4CH-Pulse Jet Sequential Timer



SPECIFICATION :

Model	DBST-04
Description	Programmable Pulse Jet Sequential Timer
Over All Size	150*110*40 mm
Enclosure Type	MS Powder Coated
Mounting Type	Flush Mounting
I/P Supply	230VAC, +/-15%,50Hz.(Others on Request)
Timing Range	Valve ON Time : 20 to 999 ms/ 00.1 Sec to 99.9 Sec (Selectable)
	Duaration Time : 999 Sec/Mins (Selectable)
Display Method	Upper Left = 2-Digit 0.56" RED 7-Segment LED display.for CH.Number
	Center = 3-Digit 0.56" RED or WHITE 7-Segment LED display.for Valve ON Time
	Upper Right = 3-Digit 0.56" RED or WHITE 7-Segment LED display.Duration Timer
Time Setting	Front Key Pad.
Number of O/Ps	1 to 16 Number (Selectable)
Control O/P	Solid State Relay (5A@230VAC)
OutPut Indication	LED Indication on the front panel for Each O/P status.
EMC Standard	EN50081-2 & EN 50082-2 Generic Stds for Industrial Environment
Safety Standards	Meets EN61010, Installation Catagory II
Operating Ambient	0°C to 55°C

Programmable 4CH-Pulse Jet Sequential Timer

Storage Temperature	-10 to +70 °C
Operating Humidity	5~80%RH Non-condensing

Heatcon Automation