

Programmable Multi Function Dual display Dosing Controller DOT-4D2



SPECIFICATION :

Model	DOT-4D2
Size	48*48*90 mm
Cut Out	44*44 mm
Mounting Type	Panel Mounting
I/P Supply	230VAC, +/-15%,50Hz. (Others on Request)
Timing Range	UP/Duration/Low/Total=999 Sec
Display Method	Upper = 4-Digit 0.39" RED 7-Segment LED display for PV
	Lower= 4-Digit 0.28" GREEN 7-Segment LED display for SV.
Time Setting	Front Key Pad.
Set Point	4- Set point.
Count Direction	UP
Start Logic	Power ON / Front Key/External Dry Contact
Cycle Reset	Front Key, Power interruption.
Control O/P	2-Nos of 1 C/O-Relay o/p (5A@230vac) each for UP & Low
Output Indication	LED Indication on the front panel for Each O/P status.
EMC Standard	EN50081-2 & EN 50082-2 Generic Stds for Industrial Environment
Safety Standards	Meets EN61010, Installation Category II
Operating Ambient	0°C to 55°C

Programmable Multi Function Dual display Dosing Controller DOT-4D2

Storage Temperature	-10 to +70 °C
Operating Humidity	5~80%RH Non-condensing

Heatcon Automation