

# Programmable Multi Function Dual display Dosing Controller LT-4D2



## SPECIFICATION :

<b>Model</b>	LT-4D
<b>Over All Size</b>	48*48*90 mm
<b>Cut Out</b>	44*44 mm
<b>Mounting Type</b>	Panel Mounting
<b>I/P Supply</b>	230VAC, +/-15%,50Hz (Other Supply on Request).
<b>Timing Range</b>	FOR/REV/HOLD=999 Sec
	Pre-Wash/Rinse/ Main Wash =999 Min
<b>Display Method</b>	Upper = 4-Digit 0.39" RED 7-Segment LED display.for PV
	Lower= 4-Digit 0.28" GREEN 7-Segment LED display for SV.
<b>Time Setting</b>	Front Key Pad.
<b>Power Fail Memory</b>	Each Cycle
<b>Start Logic</b>	Power ON / Front Key/External Dry Contact
<b>Cycle Reset</b>	Front Key , Power interruption.
<b>Control O/P</b>	3-Nos of 1 C/O-Relay o/p (3A@230vac)
<b>Output Indication</b>	LED Indication on front panel for Each O/P status.
<b>EMC Standard</b>	EN50081-2 & EN 50082-2 Generic Stds for Industrial Environment
<b>Safety Standards</b>	Meets EN61010, Installation Category II
<b>Operating Ambient</b>	0°C to 55°C

# Programmable Multi Function Dual display Dosing Controller LT-4D2

<b>Storage Temperature</b>	-10 to +70 °C
<b>Operating Humidity</b>	5~80%RH Non-condensing

Heatcon Automation