

Programmable Multi Function Dual display Dosing Controller LT-9D3



SPECIFICATION :

Model	LT-9D3
Over All Size	96*96*50 mm
Cut Out	92*92 mm
Mounting Type	Panel Mounting
I/P Supply	230VAC, +/-15%,50Hz.(Others on Request)
Timing Range	FOR/REV/HOLD=999 Sec
	Pre-Wash/Rinse/ Main Wash =999 Min
Display Method	Upper = 4-Digit 0.56" RED or WHITE 7-Segment LED display.for PV
	Lower= 4-Digit 0.39" GREEN 7-Segment LED display for SV.
Time Setting	Front Key Pad.
Set Point	6- Set point.
Count Direction	Down
Power Fail Memory	Each Cycle
Start Logic	Power ON / Front Key/External Dry Contact
Cycle Reset	Front Key, Power interruption.
Control O/P	3-Nos for 1 C/O-Relay o/p (3A@230vac) each for FOR/REV/Cycle End
OutPut Indication	LED Indication on the front panel for Each O/P status.
EMC Standard	EN50081-2 & EN 50082-2 Generic Stds for Industrial Environment

Programmable Multi Function Dual display Dosing Controller LT-9D3

Safety Standards	Meets EN61010, Installation Category II
Operating Ambient	0°C to 55°C
Storage Temperature	-10 to +70 °C
Operating Humidity	5~80%RH Non-condensing

Heatcon Automation